Feather Picker V-Belt

Specialty Belts





3

- Durable and resistant to heat, hardening, glazing, steam and moisture
- | 2 | Oversized Polyester Cord | High-modulus cord carries the horsepower load with minimum stretch. | Adds belt strength and stability during peak shock loads.
- Double Cog
 Double sided molded cogs are engineered for superior flexibility
- Raw Edge Sidewalls
 Enhanced gripping power and long
 belt life

Gripping power of raw edge sidewalls

Superior flexing of precision molded cogs

Durability of highly engineered polymer

High strength tensile cord

Resistant to heat, steam and moisture

Resistant to wear, hardening and glazing

Broad operating temperature range -50°F to +250°F

Belts are sold in matched sets of 2

- Never mix new and used belts on a drive
- Never mix belts from different manufacturers

Available in AAX and BBX sizes.

Other sizes and constructions are available as made-to-order belts

Feather Picker V-Belt

V-Belts

Part Number Example: **BBX155FP** = **BB** X 155 FP Cross Section Cogged Inside Circumference Feather Construction (inches)

Timken Feather Picker belts are made of Ethylene Propylene Diene Monomer (EPDM) which is durable, and resistant to heat, hardening and glazing. Feather Picker belts offer superior flex and load carrying capacity, resist cracking and won't stretch.

Reduce downtime and maintenance costs with premium quality Timken belts for poultry processing equipment. The feather picking machine is a critical application in poultry processing plants. Downtime on this machine alone stops the entire process. The belts that operate in this harsh environment must be reliable. Feather Picker belts are made of an advanced polymer and optimized tensile cord for improved wear resistance and long belt life. The unique double sided molded cog design is engineered for flexibility and enhanced grip in moist conditions. Feather Picker belts resist steam and moisture better than competitive wrapped belt constructions.



Belts are sold in matched sets of 2

Feather Picker Part Numbers

Part Number	Outside Circumference	Outside Circumference	Weight
	(inches)	(mm)	(lbs.)
AAX			
AAX128FP	131.3	3335	4.7
AAX142FP	145.3	3691	5.2
AAX144FP	147.3	3741	5.2
AAX146FP	149.3	3792	5.3
AAX148FP	151.3	3843	5.4
AAX161FP	164.3	4173	5.8
AAX163FP	166.3	4224	5.9
AAX184FP	187.3	4757	6.7
ввх			
BBX155FP	160.2	4069	7.6
BBX158FP	163.2	4145	7.8
BBX161FP	166.2	4221	7.7
BBX168FP	173.2	4399	8.2
BBX172FP	177.2	4501	8.4
BBX185FP	180.2	4577	9.1
BBX195FP	200.2	5085	9.5